

UHD VIDEO 75 Ohms COAXIAL CABLE



REF : HY72915RF

SPECIFICATIONS MECANIKES / MECHANICAL SPECIFICATIONS

Type de câble / <i>Cable type</i>	6 Gb Video
Températures d'utilisation / <i>Temperature range</i>	-40 °C ~ +80 °C
Rayon de courbure minimum / <i>Minimum bend radius</i>	51,5 mm (stat) / 103 mm (dyn)
Poids / <i>Weight</i>	130 kg/km

SPECIFICATIONS ELECTRIQUES / ELECTRICAL SPECIFICATIONS

Frequence d'utilisation / <i>Frequency range</i>	DC ~ 6 GHz
Impédance / <i>Impedance</i>	75 Ohms
Capacité / <i>Capacitance</i>	53 pF/m
Vitesse de propagation / <i>Velocity of propagation</i>	84 %
Efficacité de blindage / <i>Shielding effectiveness</i>	80 dB (min)
Retard linéique / <i>Time delay</i>	4.54 ns/m
Tension d'utilisation / <i>Voltage Withstand</i>	6000 V spark

CONSTRUCTION ET MATERIAUX / CONSTRUCTION AND MATERIAL SPECIFICATIONS

Conducteur central / <i>Inner conductor</i>		Solid BC Ø 1 x 1.65 mm
Diélectrique / <i>Dielectric</i>		Foam PE Ø 7.20 mm
Conducteur extérieur / <i>Outer conductor</i>		Al polyester tape Ø 7.30 mm
Tresse de blindage / <i>Shield braid</i>		Tin Plated Cu Ø 7.90 mm
Gaine et Couleur / <i>Jacket and Color</i>		LSFH Ø 10.30 mm
Caractéristiquess spécifiques / <i>Specific characteristics</i>	Max trans UHDTV	170m @ 6Gb/s
	Feu / <i>Fire</i>	Halogen free IEC60754
	Fumée / <i>Smoke</i>	EN61034-2
	Autre / <i>Other</i>	EN 50575

ATTENUATION ET PUISSANCE / ATTENUATION AND POWER HANDLING

Frequency (MHz)	5	88,5	135	180	360	750	1000	1500	2500	3000	6000
Typical attenuation (dB/m)	0,009	0,036	0,044	0,051	0,075	0,113	0,129	0,164	0,207	0,235	0,362
Typical attenuation with VSWR = 1.0 and Temperature = 25 °C											
Max power handling (W/cw)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Max power handling with VSWR = 1.0, Temperature = 40 °C, sea level, dry air, atmospheric pressure and no solar loading											

ATTENUATION (dB/m) / TYPICAL ATTENUATION (dB/m) vs FREQUENCY (MHz)

